PAVER-SAFE_

Application Instructions



- 1. PAVER-SAFE is designed for **pedestrian areas only** and its main purpose is to offer a **temporary protection** to people walking on the tile in the event of a fracture or break. For safety, always immediately close off the area of the affected tile and replace as soon as possible.
- 2. Always store PAVER-SAFE inside in a well-ventilated place away from direct sunlight and in a temperature range of 0 °C to 35 °C.
- 3. Do not install in temperatures below 0 °C.
- 4. PAVER-SAFE is best used within 9 months of manufacture after which the adhesive properties may decline. The date of manufacture can be found on the packaging.
- 5. PAVER-SAFE is only suitable for tiles 60mm wide. It can be cut to accommodate different lengths of tiles. Do not combine smaller cut sheets on one tile; always use one complete sheet per tile, cut to the appropriate size.
- 6. Clean the back of the tile so that it is free of dust, sand, loose pieces, oils and other chemicals.
- 7. Wipe off any moisture thoroughly and allow tiles to dry completely before applying PAVER-SAFE to ensure proper adhesion.
- 8. To install, remove the protective film from the back of PAVER-SAFE and then apply the sticky side to the underside of the tile using sufficient pressure with a pressure roller.
- 9. Pre-application of PAVER-SAFE can improve the adhesion when tiles are stacked according to the instruction below.
- 10. If PAVER-SAFE has been applied to tiles in advance, place the tiles on top of each other diagonally. Always stack the tiles facing the same side i.e. top to top, and underside to underside. If a top is stacked facing an underside, the top of the tile may stain and in higher temperatures, PAVER-SAFE could stick to the top of the tile. Always insert a plastic film or sheet between them to avoid any transfer of colour or adhesive. Do not leave the tiles stacked for longer than 24 hours and do not stack more than 6 tiles on top of each other.

